

SMD-49S TYPE

CRYSTAL RESONATOR, LEAD TYPE



Features

- This series applies reliable resistance-weld sealing which ensure high specification performance.
- Mature product for uses in applications which requires high levels of manual assembly such as electronic toys or home electronics and/or appliances.
- Ideal solution for DIP clock design looking to switch to SMD production without drastic changes.

STANDARD SPECIFICATION:

Items	Parameter		FREQUENCY	Mode	RR/SERIES
Frequency Range	A	B	3.0 ~ 3.6 MHz	Fund.	150ΩMax.
	3.0 ~ 75 MHz	6.0~75MHz			
Oscillation Mode Thickness Shear Mode	Fundamental; 3rd Overtone		3.7 ~ 4.2 MHz	Fund.	100ΩMax.
Frequency Tolerance (at 25°C)	±30ppm, ±50ppm, ±100ppm, or specify		4.3 ~ 6.0 MHz	Fund.	80ΩMax.
Frequency Stability Over Operating Temperature Range (Ref. to 25°C)	±30ppm, ±50ppm, ±100ppm (standard), or specify		6.1 ~ 10.0 MHz	Fund.	60ΩMax.
Operating Temperature Range	-20 ~ +75°C		10.1 ~ 14.0 MHz	Fund.	50ΩMax.
Drive Level (DL)	100μW Typ, or specify		14.1 MHz ~	Fund.	40ΩMax.
Load Capacitance (CL)	Series, 12pF, 16pF, 20pF, 32pF (Fund.) or specify. 8pF, 10pF, 12pF, 16pF (3rd) or specify		26.0 ~ 29.0 MHz	Fund.	40ΩMax
				3rd.	150ΩMax.
Storage Temperature Range	-30 ~ +80°C		29.1 ~ 40.0 MHz	Fund.	40ΩMax
				3rd.	100ΩMax.
Aging (at 25°C)	±5ppm/year Max.		40.1 ~ 75.0 MHz	3rd.	80ΩMax.

Packing Unit : 1,000pcs/Reel.

DIMENSION

Unit: mm

